



1°外部特征:(见图纸)

SCO.01.0006

Geometry:See drawing

2°初始技术特性:(试验前)

Primary Technical Properties:(before test)

电压等级: Tension and limits:		90V/20	230V/20	350V/20
直流导通电压: DC Spark-over Voltage:	100V/s	72V-108V	184V-276V	280V-420V
冲击导通电压: Impulse Spark-over Voltage:	1kV/μs	≤640V	≤700V	≤900V
绝缘电阻: Insulation Resistance:	≤90V ≥90V 50V DC 100V DC	≥10GΩ	≥10GΩ	≥10GΩ
极间电容: Capacitance:	1MHz	≤0.3pF	≤0.3pF	≤0.3pF
过保护电压: Holdover Voltage:	RC//:150Ω- 100nF;RS=330Ω	≥60V	≥80V	≥80V
辉光压降: Glow Voltage:		≤100V	≤100V	≤100V
弧光压降: Arc Voltage:		≤25V	≤25V	≤25V

3°耐流特性:(试验后满足)

Power-flow Properties:(after life test)

直流导通电压: DC Spark-over Voltage:		72V-108V	184V-276V	280V-420V
冲击导通电压: Impulse Spark-over Voltage:		≤640V	≤700V	≤900V
绝缘电阻: Insulation Resistance:		≥1000MΩ	≥1000MΩ	≥1000MΩ
交流耐流: AC discharge current:	50/60Hz,600V 5times,1s interval 3min	10A	10A	10A
冲击耐流波形: Impulse discharge current:	8/20μs +5/-5,interval 3min	10kA	10kA	10kA
冲击耐流波形: Impulse discharge current:	8/20μs 1time	25kA	25kA	25kA
冲击耐流波形: Impulse discharge current:	10/350μs 1time	2KA	2KA	2KA
冲击耐流寿命: Impulse life:	10/1000μs 300times,interval 2min	50A	50A	50A

4°产品编码:

Code:

9298101 9298157 9298115



QVGQ2.E184939

YES YES YES



REG.-Nr.40008209

注: 1.可焊接性 (NFC 20-758) 浸湿: 235℃-5秒; 耐焊接性: 260℃-10秒

Surface Mount Properties (NFC 20-758) Infiltration:235℃-5s; Wilding/Soldering Hear Resistance:260℃-10s

2.本产品符合2002/95/EC directive(ROHS);所有试验条件均满足ITU-T K.12要求。

This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

总经理 GM	总经理助理 GDTM	销售部 SD	质量部 QD	技术工程部 TD	生产部 PD	日期 Date	编码 N° Code N°
						2009-4-20	92 981 XX XX