



1°外部特征:(见图纸)

SCO.01.0051

Geometry:See drawing

2°初始技术特性:(试验前)

Primary Technical Properties:(before test)

电压等级:		2500V/20
Tension and limits:		
直流导通电压:	100V/s	2000V-3000V
DC Spark-over Voltage:		
冲击导通电压:	1kV/μs	≤3800V
Impulse Spark-over Voltage:		
绝缘电阻:	≤90V ≥90V	≥10GΩ
Insulation Resistance:	50V DC 100V DC	
极间电容:	1MHz	≤0.8pF
Capacitance:		
过保护电压:	RC//:150Ω-	≥120V
Holdover Voltage:	100nF;RS=330Ω	
辉光压降:		≤250V
Glow Voltage:		
弧光压降:		≤50V
Arc Voltage:		

3°耐流特性:(试验后满足)

Power-flow Properties:(after life test)

直流导通电压:		2000V-3000V
DC Spark-over Voltage:		
冲击导通电压:		≤3800V
Impulse Spark-over Voltage:		
绝缘电阻:		≥1000MΩ
Insulation Resistance:		
交流耐流:	50/60Hz,600V	10A
AC discharge current:	5times,1s interval 3min	
冲击耐流波形:	8/20μs	10kA
Impulse discharge current:	+5/-5,interval 3min	
冲击耐流波形:	8/20μs	25kA
Impulse discharge current:	1time	
冲击耐流波形:	10/350μs	2KA
Impulse discharge current:	1time	
冲击耐流寿命:	10/1000μs	100A
Impulse life:	200times,interval 2min	

4°产品编码:

9285538

Code:



QVGQ2.E184939



REG.-Nr.40008209

注: 本产品符合2002/95/EC directive(ROHS);所有试验条件均满足ITU-T K.12要求。

Note:This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

总经理	总经理助理	销售部	质量部	技术工程部	生产部	日期	编码 N°
GM	GDTM	SD	QD	TD	PD	Date	Code N°
						2009-5-7	92 855 XX XX